

EXPLORE E+ 1 PRO HEREN

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY

MOTOR	Giant SyncDrive Pro
BEDIENINGSUNIT	Giant RideControl Ergo
DISPLAY	Giant RideDash EVO
ACCU	Giant EnergyPak Smart 625, 36V Integrated Lithium-Ion

FRAME

MATEN	S, M, L, XL
KLEUREN	Rosewood
FRAME	ALUXX SL aluminum, Overdrive 1½ - 1¼" head tube, integrated KS18 kickstand mount
VOORVORK	SR Suntour NCX D AIR LO 63mm travel 15AH
DEMPER	N/A

ONDERDELEN

STUUR	Giant Connect XC Riser 31.8x690mm
STUURPEN	Giant Contact
ZADEL	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
ZADEL	Selle Royal Vivo Ergo Moderate Unisex
PEDALEN	Aluminum Platform

AFMONTAGE

SHIFTERS	Shimano Deore
VOORDERAILLEUR	Shimano Deore
ACHTERDERAILLEUR	Shimano Deore, 11-Speed, Shadow+
REMMEN	Shimano BR-MT410, hydraulic disc, 180mm
REMHENDELS	Shimano BL-M4100, I-spec EV
CASSETTE	Shimano CS-M5100, 11-42T, 11-Speed
KETTING	KMC e.11 Sport, e-bike optimized
CRANKSET	Forged Alloy minimal Q-factor, 36/48T
BOTTOM BRACKET	N/A

WIELSET

VELGEN	Giant eX 2, Tubeless Ready, 700c Aluminium
NAVEN	Giant eTracker, sealed cartridge bearings [F] 15mm Thru-Axle [R] 142x12 Thru-axle
SPAKEN	Sapim E-Lite [r] Race [f], e-bike optimized
BANDEN	Giant Crosscut Gravel 2, 700x45c (622x45), Tubeless Ready, Reflex
EXTRA'S	Giant EnergyPak 6A Smart Charger, Giant EnergyPak Plus range extender compatible

ACCESSOIRES

VERLICHTING	Axa BlueLine 50Lux Steady E6 frontAxa BlueLine Steady E6 rear
DRAGER	MIK rack. System bag & basket compatible

PRODUCTINFORMATIE

- Frame: ALUXX SL aluminum, Overdrive 1½ - 1¼" head tube, integrated KS18 kickstand mount
- Voorvork: SR Suntour NCX D AIR LO 63mm travel 15AH
- Shifters: Shimano Deore
- Crankset: Forged Alloy minimal Q-factor, 36/48T
- Kleuren: Rosewood

Adviesprijs: 4.099 €

GEOMETRIE

FRAME	S	M	L	XL
Zitbuis Lengte (mm)	435	485	535	585
Zitbuis Hoek	74,0°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	570	590	610	630
Balhoofdbuis Lengte (mm)	125	140	155	170
Balhoofdbuis Hoek	69,5°	69,5°	69,5°	69,5°
Vork Sprong (mm)	42	42	42	42
Naloop (mm)	91,3	91,3	91,3	91,3
Wielbasis (mm)	1112	1121	1142	1163
Liggende achtervork lengte (mm)	455	455	455	455
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	605	619	633	648
Reach (mm)	385	400	416	432
Stand Over Height (mm)	745	775	808	844
Stuur breedte (mm)	690	690	690	690
Stuurpen Lengte (mm)	60	70	80	90
Cranklengte (mm)	170	170	170	170
Wielmaat	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.