



SPECIFICATIES

| HYBRID CYCLING TECHNOLOGY | |
|---------------------------|---|
| MOTOR | SyncDrive Core, 50Nm, Powered by Yamaha |
| BEDIENINGSUNIT | RideControl Dash, full color LCD screen |
| DISPLAY | RideControl Dash, full color LCD screen |
| ACCU | EnergyPak 500Wh |
| FRAME | |
| MATEN | S, M, L, XL, XXL |
| KLEUREN | Black |
| FRAME | ALUXX Aluminum, Overdrive 1½ - 1¼" head tube, integrated KS18 kickstand mount |
| VOORVORK | SR Suntour XCM ATB Coil 29" 100mm travel, Tapered 1½ - 1¼" steerer |
| DEMPER | - |
| ONDERDELEN | |
| STUUR | Giant Connect TR Riser 31.8x690-750mm |
| GRIPS | Giant Sole-O Grip |
| STUURPEN | Giant Contact |
| ZADEL | Giant Sport |
| PEDALEN | Aluminum Platform |
| AFMONTAGE | |
| SHIFTERS | Shimano Altus |
| VOORDERAILLEUR | - |
| ACHTERDERAILLEUR | Shimano Alivio, 9-speed |
| REMMEN | Tektro HD-M275, hydraulic disc, 160/180mm |
| REMHENDELS | Tektro HD-M275 |
| CASSETTE | Shimano CS-HG200, 11-36T, 9-speed |
| KETTING | KMC e.9 Sport, e-bike optimized |
| CRANKSET | FSA Comet E-Bike crank arm set FSA MegaTooth Direct-mount 1X steel 36T |
| BOTTOM BRACKET | N/A |
| WIELSET | |
| VELGEN | Giant GX03V |
| NAVEN | Giant eTracker Sport, [F] 9mm QR [R] 135mm QR |
| SPAKEN | Stainless steel |
| BANDEN | Maxxis Rekon 29x2.4" Wire Bead 60TPI |
| EXTRA'S | EnergyPak 4A fast charger |
| ACCESSOIRES | |
| VERLICHTING | - |
| DRAGER | - |

PRODUCTINFORMATIE

- Frame: ALUXX Aluminum, Overdrive 1½ - 1¼" head tube, integrated KS18 kickstand mount
- Voorvork: SR Suntour XCM ATB Coil 29" 100mm travel, Tapered 1½ - 1¼" steerer
- Shifters: Shimano Altus
- Crankset: FSA Comet E-Bike crank arm set FSA MegaTooth Direct-mount 1X steel 36T
- Kleuren: Black

Adviesprijs: 2.399 €

GEOMETRIE

| FRAME | S | M | L | XL | XXL |
|---------------------------------|-------|-------|-------|-------|-------|
| Zitbuis Lengte (mm) | 405 | 455 | 505 | 535 | 560 |
| Zitbuis Hoek | 73,0° | 73,0° | 73,0° | 73,0° | 73,0° |
| Frame Lengte (horizontaal) (mm) | 575 | 600 | 625 | 650 | 675 |
| Balhoofdbuis Lengte (mm) | 105 | 115 | 125 | 140 | 155 |
| Balhoofdbuis Hoek | 68,0° | 68,0° | 68,0° | 68,0° | 68,0° |
| Vork Sprong (mm) | 46 | 46 | 46 | 46 | 46 |
| Naloop (mm) | 100,7 | 100,7 | 100,7 | 100,7 | 101 |
| Wielbasis (mm) | 1141 | 1167 | 1193 | 1219 | 1245 |
| Liggende achtervork lengte (mm) | 475 | 475 | 475 | 475 | 475 |
| Bottom Bracket Drop (mm) | 45 | 45 | 45 | 45 | 45 |
| Stack (mm) | 625 | 634 | 643 | 657 | 671 |
| Reach (mm) | 384 | 406 | 428 | 449 | 470 |
| Stand Over Height (mm) | 723 | 753 | 788 | 808 | 828 |
| Stuur breedte (mm) | 690 | 750 | 750 | 780 | 780 |
| Stuurpen Lengte (mm) | 50 | 60 | 60 | 70 | 70 |
| Cranklengte (mm) | 160 | 165 | 170 | 170 | 170 |
| Wielmaat | 29" | 29" | 29" | 29" | 29" |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.