



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Sport, 70Nm, Powered by Yamaha
BEDIENINGSUNIT	RideControl Ergo 2, RideControl GO integrated in D/T
DISPLAY	RideDash Evo
ACCU	EnergyPak Smart Compact 500Wh
FRAME	
MATEN	XS, S, M, L
KLEUREN	Trekking Green, Rosewood
FRAME	ALUXX Aluminum, Overdrive 1½ - 1¼" head tube, integrated KS18 kickstand mount
VOORVORK	RST VIV Air, TNL+, Lock-out, 50mm, 15x100
DEMPER	-
ONDERDELEN	
STUUR	Giant Contour GT, cable integrated, 30° back sweep 31.8mm
GRIPS	Liv Comfort Ergo Microtech Plus
STUURPEN	Giant Contour, EVO display integrated, adjustable
ZADELPEN	Suspension 2-bolt micro-adjustable, 30,9x270mm
ZADEL	Selle Royal Lift
PEDALEN	Aluminum Platform
AFMONTAGE	
SHIFTERS	Shimano Nexus 5-speed RevoShift
VOORDERAILLEUR	-
ACHTERDERAILLEUR	-
REMMEN	Shimano BR-MT200, hydraulic disc, 180mm [F/R]
REMHENDELS	Shimano BL-MT200
CASSETTE	Gates CDXtm stainless steel 26T rear sprocket
KETTING	Gates CDXtm Carbon Drive 120T CenterTrack belt
CRANKSET	Gates CDXtm CenterTrack 46T front sprocket
BOTTOM BRACKET	N/A
WIELSET	
VELGEN	Liv GX03V, 700c aluminium
NAVEN	Shimano HB-MT400 100x15mm thru-axle Disc [F], Shimano Nexus 5 Disc brake [R]
SPAKEN	Stainless steel
BANDEN	Maxxis Metro Pass 622x50, 60tpi, Wire Bead, Reflective, ECE-R75
EXTRA'S	-
ACCESSOIRES	
VERLICHTING	Giant Recon HL50, 50 lux frontAxa BlueLine Steady E6 rear
SLOT	-
DRAGER	MIK HD rack. system bag & basket compatible

PRODUCTINFORMATIE

- Frame: ALUXX Aluminum, Overdrive 1½ - 1¼" head tube, integrated KS18 kickstand mount
- Voorvork: RST VIV Air, TNL+, Lock-out, 50mm, 15x100
- Shifters: Shimano Nexus 5-speed RevoShift
- Crankset: Gates CDXtm CenterTrack 46T front sprocket
- Kleuren: Trekking Green, Rosewood

Adviesprijs: 3.749 €

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis Lengte (mm)	380	450	500	550
Zitbuis Hoek	74,0°	73,5°	73,0°	72,5°
Frame Lengte (horizontaal) (mm)	570	580	595	610
Balhoofdbuis Lengte (mm)	180	180	200	200
Balhoofdbuis Hoek	69,5°	69,5°	69,5°	69,5°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	86,9	86,9	86,9	86,9
Wielbasis (mm)	1127	1131	1141	1150
Liggende achtervork lengte (mm)	480	480	480	480
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	646	646	665	665
Reach (mm)	385	389	392	400
Stuur breedte (mm)	630	630	670	670
Stuurpen Lengte (mm)	90	90	90	90
Cranklengte (mm)	165	165	170	170
Wielmaat	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.