PROPEL ADVANCED PRO 0 AXS

SPECIFICATIES

FRAME	
MATEN	XS, S, M, M/L, L, XL
KLEUREN	Black Currant/Chrome
FRAME	Advanced-Grade Composite, disc
VOORVORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact SLR Aero XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 2.0
STUURPEN	Giant Contact SL Aero, OverDrive Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
ZADELPEN	Giant Vector, composite, -5/+15mm offset
ZADEL	Giant Fleet SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	SRAM Force eTap AXS
VOORDERAILLEUR	SRAM Force eTap AXS
ACHTERDERAILLEUR	SRAM Force eTap AXS
REMMEN	SRAM Force eTap AXS hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
REMHENDELS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM Force, 12-speed, 10x28
KETTING	SRAM Force D1
CRANKSET	SRAM Force D1 DUB, 35/48 with Giant Power Halo power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
NAVEN	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver , CenterLock, 12mm thru-axle,
SPAKEN	SAPIM CX-Ray
BANDEN	CADEX Race, tubeless, 700x25c (26.5mm), folding
EXTRA'S	computer mount, water bottle cages, tubeless prepared, 30mm max tire size

Adviesprijs: 6.999 €

GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis Lengte (mm)	500	520	545	575	595
Zitbuis Hoek	73,5°	73,0°	73,0°	73,0°	72,0°
Frame Lengte (horizontaal) (mm)	535	550	565	580	600
Balhoofdbuis Lengte (mm)	130	145	165	185	200
Balhoofdbuis Hoek	72,3°	73,0°	73,0°	73,0°	73,0°
Vork Sprong (mm)	45	45	45	45	45
Naloop (mm)	64	59,2	59,2	59,2	59,2
Wielbasis (mm)	977	980	991	1006	1020
Liggende achtervork lengte (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	68	68	65	65	65
Stack (mm)	528	545	562	581	596
Reach (mm)	383	388	393	402	412
Stand Over Height (mm)	753	770	794	821	834
Stuur breedte (mm)	400	420	420	440	440
Stuurpen Lengte (mm)	90	100	110	110	120
Cranklengte (mm)	170	172,5	172,5	175	175
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.