

DEVOTE ADVANCED PRO



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Dark Purple
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc
VOORVORK	Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8 XS:40cm, S:40cm, M:42cm, L:42cm
GRIPS	Liv All Condition
STUURPEN	Giant Contact XS:70mm, S:80mm, M:90mm, L:90mm
ZADELPEN	Giant D-Fuse SLR, composite, -5/+15mm offset
ZADEL	Liv Approach SL
PEDALEN	platform pedal
AFMONTAGE	
SHIFTERS	Shimano GRX RX-815 Di2, 2x11
VOORDERAILLEUR	Shimano GRX RX-815 Di2
ACHTERDERAILLEUR	Shimano GRX RX-815 Di2
REMMEN	Shimano GRX RX-810 hydraulic, Shimano SM-RT800 rotors [F]160mm, [R]160mm
REMHENDELS	Shimano GRX RX-810 hydraulic
CASSETTE	Shimano CS-HG800, 11-speed, 11x34
KETTING	KMC X11SL-1
CRANKSET	Shimano GRX RX-810, 31/48 XS:170mm, S:170mm, M:172.5mm, L:172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant CXR-1 Carbon Disc WheelSystem
NAVEN	Giant CXR-1 Carbon Disc WheelSystem
SPAKEN	Giant CXR-1 Carbon Disc WheelSystem
BANDEN	Maxxis Receptor, 700x40c, tubeless
EXTRA'S	tubeless prepared, 45mm max tire size

Adviesprijs: 5.599 €

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis Lengte (mm)	390	420	465	500
Zitbuis Hoek	75,0°	75,0°	74,5°	74,5°
Frame Lengte (horizontaal) (mm)	515	525	535	550
Balhoofdbuis Lengte (mm)	95	125	155	180
Balhoofdbuis Hoek	70,5°	70,5°	71,0°	71,0°
Vork Sprong (mm)	50	50	50	50
Naloop (mm)	75,9	75,9	72,5	72,5
Wielbasis (mm)	1013	1020	1022	1039
Liggende achtervork lengte (mm)	430	430	430	430
Bottom Bracket Drop (mm)	80	80	80	80
Stack (mm)	530	558	588	612
Reach (mm)	378	376	372	380
ReachToHandlebar (mm)	429	437	443	452
Stand Over Height (mm)	683	711	749	779
Stuur breedte (mm)	400	400	420	420
Stuurpen Lengte (mm)	70	80	90	90
Cranklengte (mm)	170	170	172,5	172,5
Wielmaat	700c	700c	700c	700c

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.