



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY

MOTOR	SyncDrive Core, 50Nm, Powered by Yamaha
BEDIENINGSUNIT	RideControl Ergo 2
DISPLAY	RideDash EVO
ACCU	Persoonlijke accukeuze: 300Wh, 400Wh, of 500Wh (adviesprijs op basis van 300Wh)

FRAME

MATEN	M, L, XL
KLEUREN	Gunmetal Black
FRAME	ALUXX aluminium
VOORVORK	SR Suntour NEX 50mm Suspension

ONDERDELEN

STUUR	Aluminium 30degree sweep
STUURPEN	Aluminum angle adjustable 1¼"x 90mm
ZADELPEN	Suspension 30,9x300mm
ZADEL	Selle Royal Essenza Plus
PEDALEN	Anti-slip

AFMONTAGE

SHIFTERS	Shimano 8sp Revoshift
REMMEN	Tektro HD-M285, hydraulic disc
REMHENDELS	Tektro HD-M285
CASSETTE	18T
KETTING	KMC Z1e HX, e-bike optimized
CRANKSET	Giant aluminium

WIELSET

VELGEN	Giant Double Wall Aluminum 622x19
NAVEN	Shimano HB-TX505 [F], Shimano Nexus 8 disc brake [R]
SPAKEN	Sapim Leader, stainless 14G(2.0mm) [F] Sapim Strong, stainless 13-14G(2.3-2.0mm) butted [R]
BANDEN	Banden met anti-leklaag

ACCESSOIRES

VERLICHTING	Axa BlueLine 30 LED [F] Spanninga Solo LED [R]
DRAGER	Custom design for rear battery with MIK system

Adviesprijs: 2.499 €

GEOMETRIE

FRAME	M	L	XL
Zitbuis Lengte (mm)	500	550	600
Zitbuis Hoek	72,0°	72,0°	72,0°
Frame Lengte (horizontaal) (mm)	590	610	620
Balhoofdbuis Lengte (mm)	145	160	180
Balhoofdbuis Hoek	70,0°	70,0°	70,0°
Vork Sprong (mm)	43	43	43
Naloop (mm)	82	82	82
Wielbasis (mm)	1104	1125	1135
Liggende achtervork lengte (mm)	470	470	470
Bottom Bracket Drop (mm)	60	60	60
Stack (mm)	616	630	649
Reach (mm)	390	405	409
Stuur breedte (mm)	670	670	670
Stuurpen Lengte (mm)	90	90	90
Cranklengte (mm)	170	170	170
Wielmaat	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.