



## SPECIFICATIES

| FRAME            |  |
|------------------|--|
| MATEN            | S, M, M/L, L, XL   |
| KLEUREN          | Tiger Red/Dried Chili  |
| FRAME            | Advanced-grade composite, disc   |
| VOORVORK         | Advanced-grade composite, full-composite steerer, disc                               |
| DEMPER           | N/A  |
| ONDERDELEN       |  |
| STUUR            | Giant Contact SL D-Fuse XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm           |
| HANDVATTEN       | Stratus Lite 3.0   |
| STURPEN          | Giant Contact Aero Light XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm      |
| ZADELPEN         | Giant D-Fuse, composite, 14mm offset   |
| ZADEL            | Giant Approach   |
| PEDALEN          | N/A  |
| AFMONTAGE        |  |
| SHIFTERS         | Shimano 105  |
| VOORDERAILLEUR   | Shimano 105  |
| ACHTERDERAILLEUR | Shimano 105  |
| REMMEN           | Shimano 105 hydraulic, Giant MPH rotors [F]160mm, [R]160mm                           |
| REMHENDELS       | Shimano 105  |
| CASSETTE         | Shimano 105, 11x36   |
| KETTING          | KMC X12L-1   |
| CRANKSET         | Shimano FC-RS520, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| BOTTOM BRACKET   | Shimano, press fit   |

| WIELSET |   |
|---------|---|
| VELGEN  | Giant P-R2 Disc wheelset, alloy   |
| NAVEN   | Giant alloy, 12mm thru-axle   |
| SPAKEN  | Sapim stainless   |
| BANDEN  | Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding                |
| EXTRA'S | fender mount, water bottle cages, tubeless prepared, 38mm max tire size |

Adviesprijs: 2.799 €

## GEOMETRIE

| FRAME                           | S     | M     | ML    | L     | XL    |
|---------------------------------|-------|-------|-------|-------|-------|
| Zitbuis Lengte (mm)             | 445   | 480   | 515   | 535   | 565   |
| Zitbuis Hoek                    | 74,0° | 73,5° | 73,0° | 73,0° | 73,0° |
| Frame Lengte (horizontaal) (mm) | 530   | 545   | 560   | 575   | 595   |
| Balhoofdbuis Lengte (mm)        | 140   | 150   | 175   | 195   | 215   |
| Balhoofdbuis Hoek               | 71,8° | 72,5° | 72,5° | 72,5° | 72,5° |
| Vork Sprong (mm)                | 50    | 50    | 50    | 50    | 50    |
| Naloop (mm)                     | 63,4  | 58,6  | 58,6  | 58,6  | 58,6  |
| Wielbasis (mm)                  | 994   | 998   | 1010  | 1025  | 1040  |
| Liggende achtervork lengte (mm) | 420   | 420   | 420   | 420   | 420   |
| Bottom Bracket Drop (mm)        | 75    | 75    | 70    | 70    | 70    |
| Stack (mm)                      | 541   | 558   | 577   | 596   | 615   |
| Reach (mm)                      | 375   | 380   | 384   | 393   | 402   |
| Stand Over Height (mm)          | 733   | 762   | 796   | 814   | 841   |
| Stuur breedte (mm)              | 400   | 420   | 420   | 440   | 440   |
| Stuurpen Lengte (mm)            | 90    | 100   | 100   | 110   | 110   |
| Cranklengte (mm)                | 170   | 172,5 | 172,5 | 175   | 175   |
| Wielmaat                        | 700C  | 700C  | 700C  | 700C  | 700C  |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.